DRG STATUS					ZONE	REVISION HISTORY	AUTH	DR	APVD 1	APVD 2
DATE	STG	REV	R/P	CHG						
30MR16		00				SOE 6-QW-45(350)-LTI	30343(1)	S.X	CNZ	ZDG

TOP VIEW DIMENSION ARE FROM EDGE OF COVER





上海JCI工程部核准章
审核 张金乃 日期 2016.5.30
批准 高XXX 日期 5/30.2016

APPLICATION DATA

CAT. NO. 6-QW-45(350)-LTI 12 VOLTS

Ref Name: 46B24L
GROUP SIZE: BCI____ JIS B24 EN__

PERFORMANCE RATINGS:
RESERVE CAPACITY AT 27° C: MINUTES ____ MIN
COLD CRANKING AMPERES AT -18° C 350 AMPS

20 HOUR RATE: AMP HR 45 AH

RECOMMENDED MAXIMUM CHARGING OR
OPERATING TEMPERATURE 52 °C

INSTALLATION INSTRUCTIONS:
RECOMMENDED TERMINAL TORQUE SPECIFICATIONS:
TOP TERMINAL POST 5.6-7.9 (N-m)
RECOMMENDED RETAINER TORQUE SPECIFICATIONS:
BASE CLAMP 15.0-20.0 (N-m)
TOP BAR/FRAME 2.3-4.5 (N-m)





UNLESS OTHERWISE SPECIFIED

THIS DOCUMENT IS IN ACCORDANCE WITH ASME Y14.5M-1994 AS AMENDED BY THE ISO GLOBAL DIMENSIONING AND TOLERANCING ADDENDUM-1997. ALL GEOMETRIC TOLERANCES AND RELATED DATUMS APPLY RFS. RULE #1 (PERFECT FORM AT MMC) DOES NOT APPLY WHEN RELATIONSHIP BETWEEN FEATURES IS ESTABLISHED BY ORIENTATION OR LOCATION TOLERANCES. SEPARATE POSITION CALLOUTS MAY BE MADED SEPARATELY REGARDLESS OF DATUM REFERENCES.

ALL DIMENSIONS ARE IN MILLIMETERS

ZERO PLACE DECIMALS ± 1
ONE PLACE DECIMALS ± 1
TWO PLACE DECIMALS ± .5

ANGLES ±1 DEGREE

REFERENCE

THIRD ANGLE PROJECTION

DO NOT SCALE USE MATH DATA

Johnson Controls

JOHNSON CONTROLS BATTERY GROUP, INC.
CONFIDENTIAL AND PROPRIETARY INFORMATION

		DATE
DR	S.XU	30MR16
APVD1	CN.ZHANG	
APVD2	ZG.GAO	
APVD3		
APVD4		
APVD5		

MATERIAL

DRAWING NAME: B24LTI PMV OUTLINE

DRAWING NUMBER: 30033775

SIZE	SCALE	FRAME NO	SHEET NO	STG	REV	R/P
A1	1:1	1 OF 1	1 OF 1		00	