




TOP VIEW DIMENSIONS ARE FROM EDGE OF COVER



FRONT LABEL
ON THE OTHER SIDE



DWG STATUS				ZONE		REVISION HISTORY			AUTH		OR		APVD	
DATE	SIG	REV	N/P	CHG										
11AP16		00						AFW SDE 6-QW-100(680)					5034310	5.X CNZ 208

APPLICATION DATA

CAT. NO. 6-QW-100(680) 12 VOLTS

GROUP SIZE: BCI J15 E41 EN

PERFORMANCE RATINGS:
RESERVE CAPACITY AT 27° C: MINUTES 680 MIN
COLD CRANKING AMPERES AT -18° C 100 AMPS
20 HOUR RATE: AMP HR 100 AH

RECOMMENDED MAXIMUM CHARGING OR
OPERATING TEMPERATURE 52 °C

INSTALLATION INSTRUCTIONS:
RECOMMENDED TERMINAL TORQUE SPECIFICATIONS:
TOP TERMINAL POST 5.6-7.9 (N-m)
RECOMMENDED RETAINER TORQUE SPECIFICATIONS:
BASE CLAMP 15.0-20.0 (N-m)
TOP BAR/FRAME 2.3-4.5 (N-m)

UNLESS OTHERWISE SPECIFIED
THIS DOCUMENT IS IN ACCORDANCE WITH ASME
Y14.5M-1994 AS AMENDED BY THE 2018 GLOBAL
DIMENSIONING AND TOLERANCING ADDENDUM-
1997. ALL GEOMETRIC TOLERANCES AND
RELATED DATUMS APPLY PER RULE #1
(PERFECT FORM AT MMC) DOES NOT APPLY WHEN
RELATIONSHIP BETWEEN FEATURES IS
ESTABLISHED BY ORIENTATION OR LOCATION
TOLERANCES. SEPARATE POSITION CALLOUTS
MAY BE USED SEPARATELY REGARDLESS OF
DATUM REFERENCES.

ALL DIMENSIONS ARE IN MILLIMETERS
ZERO PLACE DECIMALS ±
ONE PLACE DECIMALS ±
TWO PLACE DECIMALS ±

ANGLES ± 1 DEGREE

REFERENCE

THIRD ANGLE
PROJECTION

DO NOT
SCALE

USE MATH
DATA

3CC
IMPERIAL

Johnson Controls				DATE	
JOHNSON CONTROLS BATTERY GROUP, INC.				11AP16	
CONFIDENTIAL AND PROPRIETARY INFORMATION					
NOTE: THIS DRAWING IS INTENDED FOR REFERENCE ONLY. IT DOES NOT CONSTITUTE A CONTRACT. IT IS NOT TO BE USED FOR CONSTRUCTION OR REPRODUCTION OF ANY PARTS OR EQUIPMENT WITHOUT THE WRITTEN PERMISSION OF JOHNSON CONTROLS BATTERY GROUP, INC.					
MATERIAL					
DRAWING NAME				N100 OUTLINE	
DRAWING NUMBER				30033933	
SIZE				1:1	
SCALE				1 OF 1	
FRAME NO				1 OF 1	
SHEET NO				1 OF 1	
REV NO				00	