

FLOWSTART

UL

US

LISTED

CE

Models Available  
Upon Request

Circulates warm coolant throughout the engine to provide even heat distribution.

APPLICATION(S)

- Power Generation

TYPE OF HEATING

- Forced Flow

FEATURES

- Integrated, high efficiency pump
- Cast aluminum housing
- PA66 electrical cover
- Available power  
0.5 to 2kw  
120, 230, & 240V
- Regulating thermostat  
89-104°F (32-40°C)  
95-122°F (35-50°C)
- Safety thermostat 230°F (110°C), manual reset rated at 25A
- 6.9' (2.1m) power cable
- Mounting kit included
- 5/8" Hose Barb



| Part No.          | Old Part No. | Volts | Phase | Watts | Regulating Thermostat | Safety Thermostat | Plug Type  | Certifications |
|-------------------|--------------|-------|-------|-------|-----------------------|-------------------|------------|----------------|
| FS1201103550MFS11 | 3305106      | 120   | 1     | 1000  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA 5-15  | UL             |
| FS1201153550MFS12 | 3305114      | 120   | 1     | 1500  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA 5-20  | UL             |
| FS1201203550MFS13 | 3305122      | 120   | 1     | 2000  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA L5-30 | UL             |
| FS2081103550MFS21 | 3305130      | 208   | 1     | 1000  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA 6-15  | UL             |
| FS2081203550MFS21 | 3305138      | 208   | 1     | 2000  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA 6-15  | UL             |
| FS2301103550MFS21 | 3305146      | 240   | 1     | 1090  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA 6-15  | UL             |
| FS2301203550MFS21 | 3305154      | 240   | 1     | 2180  | 95°-122°F (35°-50°C)  | 230°F (110°C)     | NEMA 6-15  | UL             |

PRODUCT DIMENSIONS

