

THERMOSTART



APPLICATIONS

- Industrial
- Power Generation
- Light and Heavy Duty

TYPE OF HEATING

- Thermosiphon

FEATURES

- Compact and easy to install – vertical mounting
- Aluminum housing
- Available power
1.5 to 4kw120,
208, 230, 240, & 240V
50 or 60 Hz
- Regulating adjustable thermostat 32-176°F (0-80°C)
- Safety thermostat 230°F (110°C), manual reset rated at 25A
- 4.9' (150cm) power cable
- Mounting kit included



Part No.	Old Part No.	Volts	Phase	Watts	Regulating Thermostat	Safety Thermostat	Plug Type	Certifications
THS120120MTH13	3301125	120	1	2000	32°-176°F (0°-80°C)	230°F (110°C)	NEMA L5-30	UL
THS208130MTH22	3301131	208	1	3000	32°-176°F (0°-80°C)	230°F (110°C)	NEMA 6-20	UL
THS230130MTH22	3301138	240	1	3270	32°-176°F (0°-80°C)	230°F (110°C)	NEMA 6-20	UL
THS230140MTH23	3301139	240	1	4360	32°-176°F (0°-80°C)	230°F (110°C)	NEMA L6-30	UL

PRODUCT DIMENSIONS

